

— ULTIMATE —
GARAGE KIT



The Gogogate2 Ultimate Garage Kit is the latest solution from Remsol to fully control your garage. This kit includes the Gogogate2 device, a wireless sensor and an indoor IP camera for you to operate, watch and monitor the access to your garage from anywhere. All features in just one kit, including automatic open and close, door status alerts, real time video streaming with video recording. Our Gogogate2 is also compatible with Google Home and Amazon Alexa through iFTTT, making it the best choice for any Smart home.



Gogogate 2 Garage Kit Features

- Remote Access
- Status alerts
- Wireless Tilt Sensor
- User Management
- Control 3 doors with 1 device
- Calendar of events
- Visual acoustic alarm
- Multi-platform
- Easy to install
- Automatic Open/Close
- Voice Commands (USA only)
- Time to close

Indoor IP Camera Features

FEATURES AVAILABLE WITH

Gogogate2

- HD resolution (720p)**
See what can't be seen.
- Night Vision**
Watch your kids when asleep.
- Wide 116° Angle**
Panoramic view of your garage.
- Motion Detection**
Tells you if something is moving.
- Sound Detection**
Warns you of suspicious noise.
- Two-Way Audio**
Speak and listen.
- Wi-Fi (802.11 b/g/n)**
Wireless Camera.
- Free iSmartgate Cam app**
For the whole family
- Easy Set Up**
You only need your phone!



**Specs
Gogogate2 Garage Kit**

- Wi-Fi:** 802.11 b/g/n (2.4Ghz)
- SD Card:** Micro SD card 16GB Class4
- Outputs:** 3x Relay 5V DC @2A
- Inputs:** 3x Inputs for Wired sensor (Max. 60V DC @ 3A)
- Power Supply:** 100-240V AC to 5V2A
- Dimensions:** 9.5x9.5x3.7 cm
- Op° Temp°:** -10°C / +40°C
- Battery (sensor):** 2x AAA 1.5V
- RF Receiver:** 2.4Ghz / GFSK / 50m
- Sensor:** NOT WATERPROOF
- Device:** NOT WATERPROOF



**Specs
Indoor IP Camera**

- Resolution:** 1280x720 pixels (720p)
- Image:** HD Color CMOS sensor
- Night Vision:** Yes (8m)
- Motion Sensor:** Yes
- Two-Way Audio:** Yes (from App or web client)
- Wi-Fi:** 802.11 b/g/n (2.4Ghz)
- Ethernet:** RJ45 output
- Storage:** 1x micro SD card slot (max. 32GB)
- View Angle:** 116° V / 100° H
- Operating Temp°:** -10°C / +55°C (-4°F / 104°F)
- Operating Humidity:** 10%-80%
- Power Supply:** 100-240V to 5V1A
- Waterproof:** NO